

STANDARD PHRASEOLOGY

SECTION G

1. This section of standard phraseology is for general use in piping disciplines.

Hydrostatically test ____, using ____ at ____ PSIG for a minimum of ____ minutes. Allowable leakage: None.

G1

NOTE: USE ASTM F933, OR 810-5596087, SUPSHIP PORTSMOUTH STANDARD DRAWING VALVE LOCKING DEVICE (FOR CABLE LOCKING DEVICES, BUTTERFLY VALVES, AND LOCKED POSITION INDICATORS).

Install new locking devices on each valve listed in ____ in accordance with 2.____.

G2

NOTE: USE IN REPAIR OR SHIPALT WORK ITEMS FOR CLEANING NEW AND MODIFIED LEVEL II (AS DEFINED IN GSO SECTION 505K2) PIPING SYSTEMS WHICH DO NOT REQUIRE SPECIAL CLEANING REQUIREMENTS. REFER TO NOTE 1 IN GSO SECTION 505K2 FOR SYSTEMS REQUIRING SPECIAL CLEANING REQUIREMENTS.

Isolate components subject to damage and clean the new ____ piping system to a cleanliness level that results in the internal surfaces being visually free of grease, oil, flux, scale, dirt, loose particles, and any other contamination foreign to the base metal. Tap water residues on metals and light superficial rust on carbon steel surfaces, caused by a short time exposure to the atmosphere, are permitted. Light dust on cleaned surfaces is not objectionable, provided that the quantity and size of the particle does not adversely affect system operation.

G3a

NOTE: USE FOR CLEANING NEW AND MODIFIED LEVEL III PIPING SYSTEMS.

Isolate components subject to damage and clean the new ____ piping system to a cleanliness level that results in the internal system surfaces being cleaned free of contamination and any remaining residue on the surface does not interfere with the operation of or damage system components.

G3b

Restore piping flange mating surfaces exposed by disassembly of piping system. Repair by removing high spots, burrs, abrasions, and foreign matter, where removal can be accomplished by hand tools. Take precautions to maintain phonographic finish on flanges that have it.

G4

The copper-nickel piping shall be MIL-T-16420, Type __, Class ____, ____-inch wall thickness.

G5a

The carbon steel piping shall be MIL-P-24691 or ASTM A106, Grade A or B, Schedule ____.

G5b

The copper piping shall be MIL-T-24107, ____-inch wall thickness.

G5c

Purge, evacuate, and dehydrate ____ in accordance with 2.__. Charge with refrigerant ____ in accordance with 2.__.

G6

G7 PHRASE DELETED

Empty and clean ____, including piping associated with this Work Item.

G8

Align the piping to each _____. Piping shall be supported independently and shall not impose a strain.

G9a

Align the piping to each _____. Piping shall be supported independently and shall not impose a strain on the equipment.

G9b

NOTE: FOR REFERENCE USE 804-1385781, HANGERS, PIPE, FOR SURFACE SHIPS.

Install new hangers on new piping in accordance with 2.____.

G10a

Install new hangers to support the piping and prevent vibration in accordance with 2.____.

G10b

Accomplish a static head pressure test of ____ for ____ minutes. Allowable leakage: None.

G11

Accomplish tests in accordance with General Notes ____ of 2.____.

G12

G13 PHRASE DELETED

MIL-STD-777, Schedule of Piping, Valves, Fittings, and Associated Piping Components for Naval Surface Ships

G14a

802-5959353, MIL-STD-777 Modified for DDG-51 Class, Schedule of Piping, Valves, Fittings, and Associated Piping Components for Naval Surface Ships

G14b

NOTE: FOR REFERENCE USE MIL-STD-777, SCHEDULE OF PIPING, VALVES, FITTINGS, AND ASSOCIATED PIPING COMPONENTS FOR NAVAL SURFACE SHIPS.

GASKETS CONFORMING TO HH-P-151 AND MIL-G-1149 ARE PROHIBITED FOR USE IN CERTAIN APPLICATIONS AS SPECIFIED IN PSNS LTR 9505 SER 260LCM018 OF 10 MAY 2002.

New materials shall conform to 2.____, including Category and Group ____.

G15

NOTE: FOR REFERENCE USE MIL-STD-777, SCHEDULE OF PIPING, VALVES, FITTINGS, AND ASSOCIATED PIPING COMPONENTS FOR NAVAL SURFACE SHIPS.

GASKETS CONFORMING TO HH-P-151 AND MIL-G-1149 ARE PROHIBITED FOR USE IN CERTAIN APPLICATIONS AS SPECIFIED IN PSNS LTR 9505 SER 260LCM018 OF 10 MAY 2002.

Install each valve, installing new gaskets conforming to ____ and new fasteners conforming to ____.

G16

NOTE: FOR REFERENCE USE MIL-STD-777, SCHEDULE OF PIPING, VALVES, FITTINGS, AND ASSOCIATED PIPING COMPONENTS FOR NAVAL SURFACE SHIPS.

GASKETS CONFORMING TO HH-P-151 AND MIL-G-1149 ARE PROHIBITED FOR USE IN CERTAIN APPLICATIONS AS SPECIFIED IN PSNS LTR 9505 SER 260LCM018 OF 10 MAY 2002.

Install each valve, installing new gaskets and fasteners conforming to 2.____, including Category and Group ____.

G17

G18 PHRASE DELETED

G19 PHRASE DELETED

G20 PHRASE DELETED

G21 PHRASE RENUMBERED G10b

Accomplish an operational test of the new and disturbed piping at ____ PSIG. Allowable external leakage: None.

G22

Accomplish an operational test on each newly installed valve at ____ PSIG.

Cycle each valve from full closed to full open to full closed four times.
Allowable external leakage: None.

G23

NOTE: FOR REFERENCE USE S9086-RK-STM-010/CH-505, PIPING SYSTEMS.

Measure and record alignment of expansion joint piping flanges in accordance with Paragraphs 505-3.3.1 through 3.3.6.5 of 2.____.

Submit **one** legible copy, **in hard copy or electronic media**, of a report listing measurements taken to the SUPERVISOR.

G24

Nitrogen pressure test each brazed and mechanical joint at ____ PSIG for a minimum of 15 minutes.

Inspect each brazed and mechanical joint, using a soap bubble method.
Allowable leakage: None.

G25a

G25b PHRASE DELETED

Machine each seat and disc to remove hardfacing.

Weld build-up each seat and disc.

Accomplish the requirements of 009-12 of 2.a, including Table One, Column C, Lines One through 9.

Machine each seat and disc to ____.

Accomplish nondestructive testing in accordance with Line 12.

G26

Machine each seal ring seating area to remove stainless steel inlay.

Weld build-up each seal ring seating area.

Accomplish the requirements of 009-12 of 2.a, including Table One, Column H, Lines One through 9.

Machine each seal ring seating area to ____.

Accomplish nondestructive testing in accordance with Line 12.

G27

NOTE: FOR REFERENCE USE MIL-STD-777, SCHEDULE OF PIPING, VALVES, FITTINGS, AND ASSOCIATED PIPING COMPONENTS FOR NAVAL SURFACE SHIPS.

GASKETS CONFORMING TO HH-P-151 AND MIL-G-1149 ARE PROHIBITED FOR USE IN CERTAIN APPLICATIONS AS SPECIFIED IN PSNS LTR 9505 SER 260LCM018 OF 10 MAY 2002.

Install new ____ valves in place of those removed in 3.____. New materials shall conform to 2.____, including Category and Group ____.

G28a

Shop test and set each relief valve prior to installation.

Test medium shall be ____.

Seat tightness shall be ____.

Lifting pressure shall be ____.

G28b

After setting each relief valve, install wire and leadlock seals and attach a metal tag to each valve stamped with the following information:

Ship name and hull number.

Valve number or identification.

Valve lifting pressure.

Date valve tested and set.

Name of repair facility.

G28c